

A range of high quality, versatile materials microscopes widely used in industry, research and university teaching. They provide great value for money with high optical performance and robust, durable designs

## product datasheet

Routine, Research & Semiconductor Upright Materials Microscopes



GXML2003AHTG Trinocular Reflected Light Metallurgical Microscope

A robust good quality traditional metallurgical microscope equipped with a trinocular head ready for the attachment of a digital camera. This microscope includes a full set of high quality plan achromatic metallurgical objectives on a reversed objective turret. Specimens can placed on the mechanical stage with controls for XY stage and focus control. The focussing tension can be adjusted and a focus lock protects the objectives from damage. Illumination is provided from an integral 20W halogen lamp with adjustable intensity, field and aperture diaphragms, polariser and set of Y, G, B and diffusion filters.

This microscope is based on GX Microscopes L2000 series traditional microscope frame which provides a robust and a durable platform suitable for the most demanding of applications.

Options include a range of camera adapters, digital cameras, image analysis software, additional objectives and eyepieces.



#### GXML3003 Trinocular Reflected Light Metallurgical Microscope

Α high quality metalluraical microscope equipped with a trinocular head ready for the attachment of a digital camera. This microscope includes a full set of high quality plan achromatic metallurgical objectives on a modern reversed objective turret. Specimens can placed on the mechanical stage with ergonomically positioned controls for XY stage and focus control. The focussing tension can be adjusted and a focus lock protects the damage. objectives from Illumination is provided from an integral 20W halogen lamp with adjustable intensity, field and aperture diaphragms, polariser and set of Y, G, B and diffusion filters.

This microscope is built on GX Microscopes most popular and highly robust L3000 series elegant microscope frame which provides high stability and a durable platform suitable for the most demanding of applications.

Options include a range of camera adapters, digital cameras, image analysis software, additional objectives and eyepieces.




#### GXML3030 Trinocular Reflected and Transmitted Light Materials Microscope

A high quality materials microscope equipped with a trinocular head ready for the attachment of a digital camera. This microscope includes a full set of high quality plan achromatic materials objectives on a modern reversed objective turret. Specimens can placed on the mechanical stage with ergonomically positioned controls for XY stage and focus control. The focussing tension can be adjusted and a focus lock protects the objectives from damage. Illumination is provided from an integral reflected light illuminator with a 20W halogen lamp with adjustable intensity, field and aperture diaphragms, polariser and set of Y, G, B and diffusion filters. Transmitted light is from a 20W halogen lamp with adjustable intensity and field diaphragm for koehler illumination, projected through an adjustable aperture condenser on a rack and pinion with a blue and diffusion filters supplied

This microscope is built on GX Microscopes most popular and highly robust L3000 series elegant microscope frame which provides high stability and a durable platform suitable for the most demanding of applications.

Options include a range of camera adapters, digital cameras, image analysis software, additional objectives and eyepieces.







## product datasheet

Routine, Research & Semiconductor Upright Materials Microscopes



### GXML3230BD Trinocular Reflected (BF/DF) and Transmitted Light, Research Grade, Materials Microscope

A substantial, top quality materials microscope equipped with infinity optics, darkfield / brightfield incident illumination and transmitted light. It also has a trinocular head ready for the attachment of a digital camera.

This microscope includes a full set of high quality infinity BD plan achromatic materials objectives on a modern reversed objective turret. Specimens can placed on the mechanical stage with ergonomically positioned controls for XY stage and focus control. The focussing tension can be adjusted and a focus lock protects the objectives from damage.

Illumination is provided from an integral reflected light illuminator with a 50W halogen lamp with adjustable intensity, darkfield / brightfield insert field and aperture diaphragms, polariser and set of Y, G, B and diffusion filters. Transmitted light is from a 50W halogen lamp with adjustable intensity and field diaphragm for koehler illumination, projected through an adjustable aperture condenser on a rack and pinion with a blue and diffusion filters supplied

This microscope is built on GX Microscopes latest and highly acclaimed L3200 series research microscope frame which provides high stability and a durable platform suitable for the most demanding of applications.

Options include a range of camera adapters, digital cameras, image analysis software, additional objectives and eyepieces.



#### GXMXJL101A Trinocular Reflected Light Semiconductor Microscope

A highly stable, substantial microscope suitable for viewing silicon wafers, assemblies and standard metallurgical reflective specimens.

It is equipped with a trinocular head ready for the attachment of a digital camera. This microscope includes a full set of high quality plan achromatic materials objectives.

Specimens can placed on the mechanical stage with controls for XY stage movement including a rapid traverse override control, perfect for scanning over large areas.

The focussing tension can be adjusted and a focus lock protects the objectives from damage.

Illumination is provided from an integral reflected light illuminator with a 20W halogen lamp with adjustable intensity, field and aperture diaphragms, polariser and set of Y, G, B and diffusion filters

This microscope is built on GX Microscopes most substantial and highly robust XJL upright series industrial microscope frame which provides high stability and a durable platform suitable for the most demanding of applications.

Options include a range of camera adapters, digital cameras, image analysis software, additional objectives and eyepieces.



## Microscopes

### product datasheet

Routine, Research & Semiconductor Inverted Materials Microscopes



GXMXJL17AT Inverted Trinocular Reflected Light Metallurgical Microscope

One of GX Microscopes most popular metallurgical microscopes the GXMXJL17AT is simple to use, especially where you need to examine many specimens with frequent changes of polished 'micros'. The inverted microscope means that each successive specimen is immediately in focus and it is also very useful for large specimens that cannot fit under an upright microscope model.

The microscope is equipped with a trinocular head ready for the attachment of a digital camera. This microscope includes a full set of high quality plan achromatic metallurgical objectives mounted under the stage. The focussing tension can be adjusted and a focus lock protects the objectives from damage. Illumination is provided from a 20W halogen lamphouse with adjustable intensity, field and aperture diaphragms and set of Y, G, B and diffusion filters.

This microscope is built on GX Microscopes' highly robust XJL inverted series microscope frame which provides a stable and durable platform suitable for the most demanding of applications.

Options include a range of camera adapters, digital cameras, image analysis software, additional objectives and eyepieces.



GXMXJL17ATPOL Inverted Trinocular Reflected Light Metallurgical Microscope with Polarisers

Almost identical to the GXMXJL17AT model with the exception that it is provided with a retractable analyser attached to an external lever in the head of the microscope and an insertable, rotatable polarising filter can be introduced into the light path tube to provide partial or fully crossed polars.





product datasheet

## Routine, Research & Semiconductor Upright Materials Microscopes

		Specifications	• std ∘ optio	n	
			Microscope Model		
Component	GXML2003AHTG	GXML3003	GXML3030	GXML3230BD	GXMXJL101A
Trinocular Head with Phototube (requires specific camera adapter)	•	•	•	•	•
Retractable Analyser in Head	•	•	•	•	•
Pair 10X WF Eyepieces	•	•	•	•	•
Pair 16X WF Eyepieces	0	0	0	0	0
10x Eyepiece with Reticle 10mm/100 Scale Crosshair	0	0	0	0	0
Rotatable Polariser in light path	•	•	<ul> <li>Reflected</li> <li>(Transmitted optional)</li> </ul>	<ul> <li>Reflected</li> <li>(Transmitted optional)</li> </ul>	•
	non-coverslip correcte				1
5X/4X NA 0.10/0.12	4X•	5X•	5X•	5X● Infinity BF/DF	•
10x NA 0.25	•	•	•	<ul> <li>Infinity BF/DF</li> </ul>	•
20x NA 0.40	0	•	•	<ul> <li>Infinity BF/DF</li> </ul>	•
40x NA 0.60	•	0	0	<ul> <li>Infinity BF/DF</li> </ul>	•
50x NA 0.70	0	•	•		
60x NA 0.75	•	0	0	<ul> <li>Infinity BF/DF</li> </ul>	
80X NA 0.80	0	0	0	<ul> <li>Infinity BF/DF</li> </ul>	•
100X dry NA 0.85	0	0	0	<ul> <li>Infinity BF/DF</li> </ul>	
Quadruple nosepiece	•	•	•	•	
Quintuple Nosepiece	0	0	0	0	•
Stage type	Double layer mechanical 210mmX140mm Movement range: 75mmX50mm No hole	Double layer mechanical 210mmX140mm Movement range: 75mmX50mm No hole	Double layer mechanical 210mmX140mm Movement range: 75mmX50mm With hole	Double layer mechanical 210mmX140mm Movement range: 75mmX50mm With hole	Three layer mechanical 280mmX270mm Movement range: 204mmX204mm With high speed glide handle
Reflected Light Adjustable	20W •	20W •	20W •	50W •	20W •
Transmitted Light Adjustable			20W •	50W •	
Field and aperture Diaphragms, rotatable filter wheel	•	•	•	•	•
Darkfield insert				•	
Abbe Condenser on rack and pinion NA 1.25			•	•	
Camera Adapters 0.5X, 1X cmount Canon A640	0	0	0	0	0
Digital cameras up to 14MP	0	0	0	0	0
Imaging Software	0	0	0	0	0

## product datasheet

Routine, Research & Semiconductor Inverted Materials Microscopes

Specifications  ● std ○ option					
Component	GXMXJL17AT	GXMXJL17ATPOL			
Trinocular Head with Phototube (requires specific camera adapter)	•	•			
Analyser in Head		•			
Pair 10X WF Eyepieces	•	•			
Pair 16X WF Eyepieces	0	0			
10x Eyepiece with Reticle 10mm/100 Scale Crosshair	0	0			
Rotatable Polariser in light path		•			
5X NA 0.12	0	0			
10x NA 0.25	•	•			
20x NA 0.40	•	•			
40x NA 0.60	•	•			
50x NA 0.70					
60x NA 0.75	•	•			
80X NA 0.80	0	0			
100X dry NA 0.85	0	0			
Quadruple nosepiece	•	•			
Quintuple Nosepiece					
Stage type	Double layer mechanical 180mmX150mm Movement range: 15mmX15mm	Double layer mechanical 180mmX150mm Movement range: 15mmX15mm			
20W 6V Reflected Light Adjustable	•	•			
20W 6V Transmitted Light Adjustable					
Field and aperture Diaphragms	•	•			
Abbe Condenser on rack and pinion NA 1.25					
Camera Adapters 0.5X, 1X cmount Canon A640	0	0			
Digital cameras up to 14MP	0	0			
Imaging Software	0	0			